User's Guide





Model Shown: 30130-02 / 30130-02L



Transfer Chair 30130-02 / 30130-02 L

Product Identification

Model Number:

Date of Purchase:

Name of Owner / Facility:

Name of Dealer:

Dealer's Phone Number:

Midmark Europe Authorized Service Company:

Legal Notice

MIDMARK EUROPE

22, rue de Saint_Denis

B.P. 26 - 53500 ERNÉE Cedex

FRANCE


Tél.: +33 (0)2 43 05 12 70 Fax: +33 (0)2 43 05 68 99 internet: www.promotal.com

www.midmark.com

The descriptions and specifications contained in this Operating Manual are deemed correct at the time of printing.

Midmark Europe, however, reserves the right to modify its models and its procedures or render them obsolete without notice.

Before any order, we recommend that our customers consult a local sales manager.



Summary

important information	ь
Safety symbols	6
Precautions when unpacking	7
Material delivered in cardboard packaging	7
Products delivered on wooden palettes	7
Storage condition	7
Unpacking / Installation	7
Verification	7
Cleaning protocol	9
Warning	9
General maintenance	9
Disinfection	9
Maintenance Instructions	9
Painted surfaces (epoxy polyester fi nish)	9
Imitation leather coverings	10 10
Stainless steel products Chrome fi nished products	10
PVC and ABS products	10
Laminated elements	10
User's Guide – Transfer chair	11
Intended use	11
Authorisation to use	11
Patient weight capacity	11
Features	11
Dimensions	12
Using the Stretcher	13
The foot rest	13
Adjusting the foot rest	13
The brakes	13
Using the brakes	13
The arm rest	13
Adjusting the arm rest	13
Patient file holder	14

Summary

ccessories	15
Urine bag support	15
Installing the urine hag support	15
Pair of clamps	15
Installing the clamps	15
Support tray	16
Installing the Support tray	16
Using Swing IV $^{\mathbb{R}}$	16
I.V. pole with two hooks	17
Installing the IV pole	17
Auto-blocking I.V. pole	17
Installing the IV pole	17
Adjusting the height of the IV pole	17
Head rest	18
Installing the Head rest	18
Installing the head rest	18
Swing IV® (Rotating IV pole)	19
Installing Swing IV ** (rotating IV pole)	19
Installing Swing IV $^{\circ}$ (rotating IV pole)	19
Using Swing IV $^{\text{\tiny{IR}}}$	20
Safety belt	20
Using the Safety belt	20
Installing the Safety belt	21
Leg-rest	22
Installing the leg rest support	22
Storing the leg rest	22
Placing the leg-rest in a horizontal position (PH)	23
Placing the leg-rest in an inclined position (PI)	23
Oxygen bottle holder	24
Installing the Oxygen bottle holder	24
Installing the Oxygen bottle Changing the Oxygen bottle	24 25
0 0 00	
Chairs locks	25 25
Installing the chair lock Using the chair lock	25 25
Osing in than wir.	2)

Summary

Lifespan	26
Exchangeable components	26
Obligatory/specific maintenance	26
End of the device's useful life	26
Maintenance notebook	27
Note	28
Warranty Information	30
Warranty	30
Obligations	30
Exclusions	30
Exclusive Remedy	30
No Authorization	30
Declaration of Conformity	31

Safety symbols



Warning sign

The information marked with this symbol must be read and strictly followed!

Note

Procedure, practice, or condition.



Proper shipping orientation



Keep dry



Fragile



Maximum stacking height (palletted units)



General safety awareness



Refer to user guide/ operator manual



CE marking



Do not use the footrest as a step



Do not sit on the armrests



Do not sit on the leg-rest



Warning

The warning pictograms and signs installed by the manufacturer must not be removed! The manufacturer's responsibility is cancelled if these signals are removed.

Manuel d'utilisation 6

Precautions when unpacking

Material delivered in cardboard packaging

 Small, lightweight, easy to handle materiel

In this case, the products can be easily handled without any lifting gear, taking care to position the product according to the directional arrows on the packaging.

In the absence of arrows indicating the top and bottom, use the position of the various product identity labels which are always placed at the top. Heavy or cumbersome material requiring the use of lifting gear

In this case, it is possible to use a fork lift truck, provided it is used correctly.

Before moving, ensure the material is properly positioned, and that the load is evenly balanced.

Products delivered on wooden palettes

Products placed on a wooden palette may easily be moved using a forklift truck, provided this is used correctly. Before moving, ensure the truck is correctly positioned in relation to the palette, and that the whole is stable. Take additional caution when handling very tall or high articles (eg. cupboards).

Storage condition

Ambient Temperature Range : Relative Humidity :

Atmospheric Pressure:

The following conditions must be observed when storing any material:

- The area must be clean, well ventilated and be of a normal temperature.
- Store products away from the elements, and away from direct sunlight.
- The area must not be damp.

-5 °C to +38 °C (+23 °F to 100 °F) 10 % à 90 % (non-condensing) 0.5 bar to 1.05 bar (500 hPa to 1050 hPa)

- The products must not be subject to bumps or jolts.
- Do not store in an area where people are likely to pass.
- Articles must not be stacked on top of each other.
- Articles must remain in their original packaging until fi nal delivery.

Unpacking / Installation

When installing, remove all staple clips and carefully remove the cardboard packaging. Fragile parts of the product (upholstery coverings, plastic casings, etc.) may be just below the packaging. Care must be taken with cutting instruments.

Once the packaging has been removed, remove any remaining protective covering.

In the case of packaging on a wooden palette, remove the packaging as above. Depending on the model, the product is fi xed either by screwed fl anges, or by nailed wooden stakes. Use a spanner (for metal fl anges). Use a claw hammer (for wooden stakes). Lift the article off the palette, and remove the remaining protective covering. The product is now ready for use.

Verification

After unpacking the device, follow the steps below:

Check the delivery documents to make sure that the consignment is complete.

Check the external components and look for possible transport damage.

Check that the package contains the device, the accessories and options, the power cord (if electric DM) and the Operating guide.

Precautions when unpacking

Note:

Authorized CE representative

Countries in the EEC should direct all questions, incidents, and complaints to Midmark Europe's Authorized CE representative listed below:

Midmark Europe 22, Rue De St. Denis 53500 Ernée, FRANCE

Téléphone : + 33 (0)2 430 517 76 Fax : + 33 (0)2 430 572 00

Cleaning protocol

Warning

You must read the installation instructions, technical instructions, and instructions for use before handling this equipment. The instrument must be used only for the specific purpose for which it is designed, and which is described in our literature. The assembly and connection to the mains must be carried out by qualified personnel.

Under no circumstances must electrical parts (motor, unit housing the electrical control systems, control unit, adaptor etc.) be opened. MIDMARK EUROPE cannot be held responsible for any damage resulting from the instructions not being followed.



Any modification of the DM without the manufacturer's written authorisation is prohibited.



Caution

Only those accessories allowed and provided by Midmark Europe for this DM may be used.

General maintenance

Apart from regular cleaning, our products do not require regular maintenance.

The mechanical parts used as blocking mechanisms (smooth arch, notched arch, ratchet mechanisms, etc.) do not require any specific attention. The gas springs on tables do not require any maintenance. Their shaft must be kept clean, must not be subject to jolts or hard knocks, and must not be cleaned with any corrosive products. The electric and hydraulic jacks do not require any particular attention.

The variable height tables, chairs and trolleys are equipped either:

- With arms fi tted with self lubricating articulation rings.
- With telescopic bearing runners. In this
 case they should be lubricated once a
 year (particularly if the runners are noisy)
 with ordinary grease. (See the exploded
 drawings for access to the runners).

Disinfection

This Medical Device must be regularly disinfected by products which qualify as Bactericides, Virucides and Fungicides.

Maintenance Instructions

Painted surfaces (epoxy polyester fi nish)

The use of ordinary cleaning products, eg. window cleaning products, is perfectly suitable for cleaning surfaces fi nished in epoxy polyester. The following products are not recommended as they will damage these surface:



Cleaning protocol

Imitation leather coverings

Use a damp cloth and soapy water (eg. household soap). For stubborn stains, dab, but do not rub, using a cloth soaked in white spirits or in a solution of water and alcohol (less than 30 % strength).

It is not recommended to use the following: Pure alcohol, acetone, perchlorethylene, trichlorethylene, all solvants and detergents, any abrasive cleaning agents, any kind of wax.

Flame retardort classifi cation: All our coverings class are M2 or M1. We can provide you with a manufacturers certificate on request.

Stainless steel products

Cleaning and Maintenance: For maintenance of stainless steel products, periodic cleaning of the surface is sufficient. This operation is necessary to keep the products clean, but is facilitated by the quality of stainless steel surfaces. A large range of products and cleaning methods may be used. The choice products method will depend on the nature of the marks or on the product content, and on the conditions of use of the stainless steel elements.

Cleaning agents

- a) Detergent washing liquids: All types of detergents, washing liquids and commercial soaps may be used, provided they do not contain any chlorine products.
- b) Abrasive powders: These products may scratch the stainless steel surface, thereby changing the way its appearance. They should therefore not be used.
- c) Solvent: May be useful in getting rid of grease marks. The usual solvents (benzene, methylene chloride, white spirits etc.) as well as domestic or specially prepared industrial products may be used. Naturally their use requires certain precautions to be taken because of their flammable and toxic properties. Precautions must also be taken to avoid damaging adjacent materials which may be sensitive to their chemical action (paints, mastics, joints etc.).
- d) Acid products: Vinegar (acetic acid) may be used to get rid of stains made by calcium deposits. Its contact with the surfaces must be of a very limited duration, and the surface must then be thoroughly and carefully rinsed with clean water. The use of chlorine based products could damage this equipment.
- e) Bases: Not recommended.

Others: The use of steel wool or metal sponges could damage the surfaces of the products.

Chrome fi nished products

Cleaning and Maintenance: It is through important, in order not to damage this protective coating, abrasive and / or corrosive products the use of. The use of commercial cleaning products, such as window cleaning products, are safe for chrome coated surfaces. If necessary, an appropriate disinfectant may be used on chrome (make sure the instructions are followed).

PVC and ABS products

Cleaning and Maintenance: The use of commercial cleaning products, such as window cleaning products, are safe for PVC and ABS surfaces. To restore up an old or dull surface, plastic restorer products may be used. Please note that the use of any solvants or any abrasive products is could damage these surfaces.

I aminated elements

Cleaning and Maintenance: As for PVC. Use window cleaning products.

User's Guide – Transfer chair



Intended use

This Medical Device is designed for transferring a patient in a sitting position, within a health establishment, by and under the surveillance of a health professional.

This appliance must not be installed in domestic premises.

Authorisation to use

Only health professionals (doctors, caregivers) and/or qualified members of the technical staff can handle or use the couch.

Patients and companions must not intervene directly on the couch. They must not have access to the couch controls.

Patient weight capacity



Features

2 widths 47 or 60 cm

Electrogalvanized steel frame with

light grey epoxy finish

Epoxy finished push bar

Backrest and seat in class M1 flame

retardant covering

Patient file holder

Clothes basket

Adjustable arm rests

Retractable footrest


Rear castors ø 300 mm with centralized brakes


Front castors ø 100 mm – ball bearing

58 cm seat height




Dimensions (30130-02)






Dimensions (30130-02L)



Using the Stretcher

The foot rest

Adjusting the foot rest





The brakes

Using the brakes

Press your foot on the brake pedal (red R). The back castors are blocked.

To unlock the brakes, press on the central pedal (green V). The castors are free.



The arm rest

Adjusting the arm rest



For safety reasons , and in order to avoid malfunctioning, no objects should be placed between the backrest and the moving arm rest of the chair.







13 User's Guide User's Guide 13

Using the Chair

Patient file holder

Dimension useful: 43 x 23 x 3,7 cm






Urine bag support

(reference 30140-01)

Installing the urine bag support
Unscrew slightly the screws situated under the upholstery.

Insert the support and rescrew.






Pair of clamps

(reference 30148-20)

Installing the clamps



Support tray

(reference 30142-01)

Installing the Support tray

Unscrew the screw handle.
Insert the Support tray pole and rescrew.



Caution

Clamps are necessary to install these accessories.

(ref.: 30148-20)



The Support tray positions only on the right clamps of the chair.



Tighten screws before use

Using Swing IV®

For use the Swing IV®;

- 1. Unscrew the screw handle,
- 2. Lift the Support tray,
- 3. Pivot 90°.

To pivot the Swing IV®. (indicated page 20)

To reposition the Support tray after the adjustment of the Swing $\mathrm{IV}^{\text{\tiny{ID}}}$.



I.V. pole with two hooks

(reference 30148-01)

Installing the IV pole

Hold the I.V. pole, and unscrew the screw handle. Adjust the pole sliding it into the holder. Tighten the screw handle.




Caution

Clamps are necessary to install these accessories.

(ref.: 30148-20)



Tighten screws before use




Auto-blocking I.V. pole

(reference 2985-01)

Installing the IV pole

Unscrew the screw handle. Insert the I.V. pole and rescrew.





Caution

Clamps are necessary to install these accessories.

(ref.: 30148-20)




Tighten screws before use

Adjusting the height of the IV pole

The IV pole has 1 sliding stem.


Use the screw to adjust the height of the lower stem and the bolt to adjust the upper stem.






Installing the head rest (when the Swing IV^{30} is already installed)

Unscrew the Swing IV $^{\otimes}$, insert the head rest in front of the IV pole and screw together.



N°4 Allen key




Using Swing IV®

Lift the IV pole, and pivot 180°.

To lock, replace the IV pole in its casing.



Ensure the IV pole is correctly in place before use.



Safety belt

(reference 30143-01)
Using the Safety belt









Ensure to lock correctly before use


Installing the Safety belt


1. Remove the upholstery




2. Insert the lower part of the bett between the frame and the upholstery.


Replace the upholstery.







The upper part of the belt is placed on the backrest. Several possibilities, follow the same procedure as installing Swing IV $^{\text{\tiny{\$}}}$ and the head rest.














(reference 30145-02)

Box spanner of 10

Installing the Oxygen bottle holder










Also tighten the leg rest support, if this is already installed.

Installing the Oxygen bottle










Changing the Oxygen bottle

(Reference 30147-20)







Chairs locks



Lifespan

This material was designed for a lifespan of 10 years (except for wearing parts) in normal working conditions. This duration may change depending on frequency of use.

The condition of transfer thair should be checked at least once a year.

Exchangeable components

For service on the product, please contact your nearest dealer and give him the serial number and model number shown in the label (see page 2).

Obligatory/specific maintenance

Once per year:

- •Check the screws and the rods.
- · Check the articulated parts.
- Check the structure did not undergo any deformation.
- · Control the various connections.
- Note this information and the date in the maintenance notebook.

End of the device's useful life

Your dealer is responsible for reclaiming and processing this device at the end of its service life.

Do not hesitate to contact Midmark Europe, if necessary. We will suggest to you a solution to process this equipment in the best conditions.



Equipment warning

All mattresses with torn covers must be promptly replaced in order to guarantee optimum functionality of this DM.



Material warning Do not dismount the equipment

If a defect is detected, immediately contact your retailer or the aftersales department of your retailer (cf Warranty Information) for a complete diagnosis. If a doubt remains, do not use the equipment.

MAINTENANCE NOTEBOOK

	_					
	Type of intervention - corrective action					
Product Reference : Serial number (cf. label) : Manufacturing date (start date of warranty) :	Name of technician					
	Date					

If the product is returned to the retailer or manufacturer, please clean and disinfect the material.

Note

Warranty Information

Warranty

Midmark Europe warrants, to the original purchaser, products manufactured by Midmark Europe and components to be free from defects in materials and workmanship for a period of two (2) years* from the date of purchase.

Obligations

Midmark Europe will, at its discretion and expense, replace defective parts reported to Midmark Europe within the applicable warranty period, and which, upon examination by Midmark Europe, prove to be defective.

In accordance with CE regulation, Midmark Europe's distributor is responsible for after sales service during and after the warranty period.

Exclusions

- This warranty does not extend to:
 - (1) Spare parts and consumables.
 - (2) Travel and labour expenses.
 - (3) Breakdowns due to improper use, manifest neglect, or to moving the device.
 - (4) Equipment whose original characteristics have been changed by the user.
 - (5) Control units, hydraulic and electric jacks if opened by the user (seals broken).
 - (6) Damage, breakdowns, failures, or defects attributable to outside causes (lightning, electric surges, floods, natural catastrophes, impacts, etc.) or to the presence of foreign objects.
 - (7) Damage caused by improper hook-up or by the power supply, damage caused by corrosion or by gradual deterioration of the product.
 - (8) Indirect damage related to loss of use and penalties generated by poor performance.
 - (9) Aesthetic damage incurred by the outside parts of the equipment, which does not hinder proper operation, such as scratches, chips, and scrapes.
 - (10) Devices whose serial number has been rendered illegible or has been changed or removed

Exclusive Remedy

Midmark Europe's only obligation under this warranty is the replacement of defective parts. Midmark Europe shall not be liable for any direct, indirect, special, incidental, exemplary, or consequential damages or delay, including, but not limited to, damages for loss of profits or lose of use.

No Authorization

No person or firm is authorized to create for Midmark Europe any other obligation or liability in connection with the products.

THIS WARRANTY IS MIDMARK EUROPE'S ONLY WARRANTY AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED.

Upholstery sets are warranted 1 year from manufacturing defaults.



DECLARATION OF CONFORMITY



Manufacturer's name : **Midmark Europe**

Manufacturer's address : 22, rue de St. Denis de Gastines

53500 Ernée FRANCE

Year of CE marking : 2007

Product references : 30130-02 / 30130-02L

Carry a CE label.

Product Description : Transfer Chair

This mark certifies that this class I medical device:

complies with the regulation measures defined by the essential health and safety requirements of the EEC directive 93/42, appendices I and VII (decree 95-292 of the 16th March 1995).

complies with all European standards applicable to it.

Ernée.

01st, September 2012

Hugues CATTAERT Managing Director



MIDMARK EUROPE - FRANCE www.promotal.com
DIC30130-02_0614EN

